



999.00 EUR

incl. 19% VAT, plus [shipping](#)



The HBFHP792X series is a ruggedized fanless automation PC. The DIN-rail mounting form factor is suitable to be used in control cabinet for industrial automation application. There are four models that can choose according to IO requirements.

	HBFHP792L-2807-G	HBFHP792G-2807-G	HBFHP792C-2807-G	HBFHP792U-2807-G
Part No	– HBFHP792L-2807-G – HBFHP792LW-2807-G (WIFI)	– HBFHP792G-2807-G) – HBFHP792GW-2807-G (WIFI)	– HBFHP792C-2807-G – HBFHP792CW-2807-G (WIFI)	– HBFHP792U-2807-G – HBFHP792UW-2807-G (WIFI)
CPU/Chipset	– Intel® Bay Trail N2807 Processor			
Memory	– 2GB DDR3L-1333 on board memory			
Storage	– 1 * full-size Mini-PCIe slot (for MSATA)			
Network	– 2 * Intel® GbE (MB / Intel i210IT)			
Expansion slot	– 1 * M.2-2230 slot (for WiFi expansion) WiFi card – Support IEEE 802.11a/b/g/n/ac Wireless LAN 2T2R and Bluetooth 4.2 – Support 802.11ac 2x2, Wave-2 compliant with MU-MIMO			
Standard I/O	– 1 * Power button , 1 * Power LED , 1 * HDD LED – 1 * USB 3.0 , 1 * USB 2.0 – 1 * VGA , 2 * RJ45 (support WOL) – 1 * DC-In jack (Lock type)			
Expansion I/O	HBFHP792L-2807-G	HBF		