

2049.00 EUR

incl. 19% VAT, plus [shipping](#)



- NVIDIA® Jetson Orin NX !
- FANLESS !
- 16GB !
- 2x HDMI / 2x LAN !

- Applies to NVIDIA® Jetson Orin™ NX module
- 2 x M.2. for WIFI and SSD
- 2 x GbE RJ-45 (Optional: Ethernet 1 for PoE)
- 3 x USB 3.2 & 1 x HDMI output
- 20-pins expansion header
- Operating temperature -25°C~60°C
- Dimension: 126mm x 96mm x 73.9mm

AVerMedia's AI Box PC D115WOXB equips powerful NVIDIA® Jetson Orin™ NX module. This efficient system-on-module (SoM) opens new worlds of embedded IoT applications with full analytic capabilities.

D115WOXB Box PC is designed for the industry applications with spatial concern and feature a rich assortment of I/O ports for rapid AI-based solution development and seamless deployment as required by demanding business applications.

AVerMedia supports businesses of all sizes and offers customizable BSP services, flexible MoQ, in addition to NVIDIA's JetPack™ SDK.

Stay Ahead with AVerCooler – Achieving 5°C Lower Operation under Others' Regular Workload for Enhanced NVIDIA Jetson Efficiency, Extended Lifespan, and Superior Performance.

**Type / Model**  
**NVIDIA GPU SoC Module Compatibility**  
**Networking**  
**Display Output**  
**Temperature**

**Box PC / D115WOXB-16G**  
**NVIDIA® Jetson Orin NX module**  
**2x GbE RJ-45**  
**1xM.2. key E 2230 for wifi**  
**1 x HDMI output3840 x 2160 at 60Hz for Orin NX**  
**Operating temperature -25°C~60°C**  
**Storage temperature -40°C ~ 85°C**  
**Relative humidity 40 °C @ 95%, Non-Condensing**

---

|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| MIPI Camera Inputs(Internal)    | 2x 4 lane MIPI CSI-2, 22 pin FPC 0.5mm Pitch Connector                  |
| USB                             | 1x USB 2.0 type C for recovery<br>3x USB 3.2 Type-A (1xUSB is internal) |
| Storage                         | 1x M.2. key M 2280 for NVMe (256G SSD installed in box PC)              |
| Expansion Header (Internal)     | 20 pins: 2x I2C, 1x UART, 4x GPIOs, 1xCAN (EU terminal block)           |
| Power requirement               | DC in JACK on board & ATX 4pin<br>12V/5A, 12V~24V is recommended..      |
| Power Cord                      | US/JP/EU/UK/TW/AU/CN                                                    |
| Fan Module                      | Fanless Solution                                                        |
| Buttons                         | Power and Recovery                                                      |
| RTC Battery                     | Support RTC battery and Battery Life Monitoring by MCU                  |
| PCB/Electronics Mechanical Info | W: 126mm (W) x 96mm (L) x 74mm (H)<br>Weight: 1kg                       |
| Certifications                  | CE, FCC, KC                                                             |
| Package                         | 1x D115WOXB (256G SSD installed)<br>1x Adapter and Power cable          |